

Product Datasheet

06 Downlights Fixed LED>The Dark Light Downlights Aluminium

10108ED/W/BS/W



8W COB LED recessed downlight, for general lighting applications.

Complete with 300mA driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads	Dimensions
	95mm 60mm

Physical Specification

Item Group	06 Downlights Fixed LED
Family	The Dark Light Downlights Aluminium
Order Code	10108ED/W/BS/W
Colour	White-Brass
Material	Aluminium
Shape	Circular
Height	60mm

Diameter	95mm
Cutout Hole Diameter	75mm
Recessed Ceiling	Yes
Depth Required	80mm
Indoor	Yes



No

Electrical Characteristics

Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	8W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	300mA
Voltage	20V
Safety Class	
Power(Watts)	6W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2835

LED Brand	Sanan
LED Number	1
F Mark	F
Gear	
Gear Type	Led Driver



Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	4,2-7,2W
Power Factor	0,5
Constant Current	Yes
300mA	14-24V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	LIFUD

Illumination Data

Colour Temperature	_
Lumen Output	
Light Efficiency	_
CRI	
Beam Angle	_
Illumination Diagram	
Dark Light	

3000K	
560lm	
70lm/W	
80	
60°	
Yes	

Packing Info	
Box Length	11,5cm
Box Width	11,5cm

Box Height	8cm
Box Weight	0.254kg
Pcs/Carton	50
Barcode	5291889058632



Certification & Warranty

Warranty

2 years

switch to one light!



