

02 Recessed Spots Fixed LED>The Dark Light Pro Range Aluminium

10110FD/W/W



10W COB LED recessed spot, IP20, for general lighting applications.

Supplied with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery






Physical Specification

Item Group	02 Recessed Spots Fixed LED
Family	The Dark Light Pro Range Aluminium
Order Code	10110FD/W/W
Colour	White
Material	Aluminium
Shape	Circular
Height	100mm

Diameter	75mm
Cutout Hole Diameter	68mm
Recessed Ceiling	Yes
Depth Required	130mm
Indoor	Yes
Adjustable	No

Electrical Characteristics

Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	10W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	

Fitting	
Input Type	Constant Current
Input Current	300mA
Voltage	30V
Safety Class	
Power(Watts)	9W
IP Rating	IP20
Light Source	LED built in
LED Type	COB
LED Brand	Epistar

LED Number

1

F Mark



Gear

Gear Type

Led Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Power(Watts)

7,5-12,6W

Power Factor

0,9

Constant Current

Yes

300mA

25-42V

IP Rating

IP20

Safety Class



Dimmable

No

Housing Material

Plastic

Brand

LIFUD

Illumination Data

Colour Temperature

3000K

Lumen Output

800lm

Light Efficiency

80lm/W

CRI

90

Beam Angle

24°

Illumination Diagram



Dark Light

Yes

Packing Info

Box Length

11cm

Box Width

9cm

Box Height	12cm
Box Weight	0.264kg
Pcs/Carton	50
Barcode	5291889057369
HS Code	9405413990

Certification & Warranty

Warranty	3 years
----------	---------

switch to
one light!

one
LIGHT

