



Product Datasheet

06 Downlights Fixed LED>The SMD Dark Light Range

10122D/W/C



22W Dark Light LED Downlight .

Supplied with 500mA non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions





55mm

Physical Specification

Item Group	06 Downlights Fixed LED
Family	The SMD Dark Light Range
Order Code	10122D/W/C
Colour	White
Material	Die Cast
Shape	Circular
Height	55mm
Diameter	175mm
Cutout Hole Diameter	165mm
Recessed Ceiling	Yes
Depth Required	75mm
Indoor	Yes

Electrical Characteristics

Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	22W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	500mA
Voltage	40V
Safety Class	
Power(Watts)	20W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Sanan
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes

60 Hz	Yes
Power(Watts)	12,5-20W
Power Factor	0,9
Constant Current	Yes
500mA	25-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	-30? ~ +50?
Housing Material	Plastic
Brand	Lifud
Illumination Data	
mammatori Bata	
Colour Temperature	4000K
Lumen Output	1870lm
Light Efficiency	85lm/W
CRI	90
Beam Angle	100°
Illumination Diagram	
Dark Light	Yes
Packing Info	
Box Length	20cm
Box Width	7cm
Box Height	18cm
Box Weight	0.630kg
Pcs/Carton	20
Barcode	5291889060741
HS Code	9405413990

Warranty 2 years

switch to one light!

