




# **Product Datasheet**

06 Downlights Fixed LED>The Frameless IP65 Range Die cast + PC

10130CF/W



30W LED frameless downlight, IP65. Suitable for Indoor/Outdoor installation and bathroom.

Complete with 700mA driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



### Gallery



### **Physical Specification**

Item Group	06 Downlights Fixed LED
Family	The Frameless IP65 Range Die cast + PC
Order Code	10130CF/W
Colour	White
Material	Die Cast
Diffuser Material	PC
Shape	Circular

Height	22mm
Diameter	215mm
Cutout Hole Diameter	195mm
Recessed Ceiling	Yes
Depth Required	50mm
Indoor	Yes
Outdoor	Yes
Adjustable	No
IK Rating	8
Electrical Characteristics	
Gear	External-Included
Fitting + Driver	
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	30W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	700mA
Voltage	36V
Safety Class	
Power(Watts)	25,2W
IP Rating	IP65

Light Source	LED built in
LED Type	SMD 4014
LED Brand	Zhaochi
F Mark	F
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	21-28W
Power Factor	0,9
Constant Current	Yes
700mA	30-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	KEGU
umination Data	
Colour Temperature	3000K
Lumen Output	2400lm
Light Efficiency	80lm/W
CRI	80
Beam Angle	120°
Illumination Diagram	

# Packing Info

Box Length	28cm
Box Width	25cm
Box Height	3cm
Box Weight	0.770kg
Pcs/Carton	20
Carton Length	57cm
Carton Width	37cm
Carton Height	28cm
Carton Weight	15,7Kg
Barcode	5291889057123
HS Code	9405413990

## Energy Label



Energy Class

**Energy Consumption** 

F

30kWh/1000h

### Certification & Warranty

Warranty

2 years

# switch to one light!

