

04 Recessed Spots Adjustable LED>The 12W COB Range

11112/AL/W



12W COB LED Recessed Adjustable Spot.

Requires 700mA driver.

Complies with standard EN60598-1 and any other specific standards



Downloads



Dimensions



Gallery



Must be ordered separately



89015A



89015AT

Physical Specification

Item Group	04 Recessed Spots Adjustable LED
Family	The 12W COB Range
Order Code	11112/AL/W
Colour	Aluminium
Material	Natural Aluminium
Shape	Circular
Height	85mm
Diameter	85mm
Cutout Hole Diameter	78mm
Recessed Ceiling	Yes
Depth Required	90mm
Indoor	Yes
Adjustable	1 Direction

Electrical Characteristics

Fitting	
Input Type	Constant Current
Input Current	700mA
Voltage	14-16V
Safety Class	III
Power(Watts)	12W
IP Rating	IP20
Light Source	LED built in

LED Type
LED Brand
LED Number
Cable Length
F Mark

COB

Epistar

1

40cm



Illumination Data

Colour Temperature
Lumen Output
Light Efficiency
CRI
Beam Angle
Illumination Diagram

3000K

1100lm

91,67lm/W

80

38°



Packing Info

Box Length
Box Width
Box Height
Box Weight
Pcs/Carton
Barcode
HS Code

11cm

9cm

9cm

0,304Kg

50

5291889038962

9405409900

Certification & Warranty

switch to
one light!

one
LIGHT

