

04 Recessed Spots Adjustable LED > The IP65 COB Dark Light Range

11112P/W/W



12W IP65 Dark light COB LED Recessed Adjustable Spot.

Requires 700mA driver.

Complies with standard EN60598-1 and any other specific standards



Downloads



Dimensions



Must be ordered separately



89015A

Related items



89015AT

Physical Specification

Item Group

04 Recessed Spots Adjustable LED


Family	The IP65 COB Dark Light Range
Order Code	11112P/W/W
Colour	White
Material	Aluminium
Shape	Circular
Height	80mm
Diameter	85mm
Cutout Hole Diameter	72mm
Recessed Ceiling	Yes
Depth Required	100mm
Indoor	Yes
Outdoor	Yes
Adjustable	1 Direction

Electrical Characteristics

Fitting

Input Type	Constant Current
Input Current	700mA
Voltage	18,5V
Safety Class	
Power(Watts)	12W
IP Rating	IP65
Light Source	LED built in
LED Type	COB
LED Brand	Bridgelux
LED Number	1
Cable Length	40cm
F Mark	

Illumination Data

Colour Temperature	3000K
Lumen Output	1100lm
Light Efficiency	91,67lm/W
CRI	90
Beam Angle	40°
Illumination Diagram	
Dark Light	Yes

Packing Info

Box Length	10cm
Box Width	9cm
Box Height	10,5cm
Pcs/Carton	48
Barcode	5291889070092
HS Code	9405409900

Certification & Warranty

Warranty	5 Years
Weee Directive	Yes

switch to
one light!

one
LIGHT

