

13 Wall & Ceiling LED>Adjustable Display Spots

12108LA/W/W



8W COB LED adjustable ceiling downlight, ideal for residential and commercial illumination.

Complete with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

Item Group	13 Wall & Ceiling LED
Family	Adjustable Display Spots
Order Code	12108LA/W/W
Colour	White
Material	Aluminium
Shape	Circular
Height	40mm
Diameter	78mm
Surface Ceiling	Yes
Surface Wall	Yes
Indoor	Yes
Adjustable	2 Directions

Gear

Built In

Fitting + Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Safety Class



Power(Watts)

8W

IP Rating

IP20

Light Source

LED built in

Dimmable

No

F Mark



Fitting

Input Type

Constant Current

Input Current

700mA

Voltage

9V

Power(Watts)

6,3W

IP Rating

IP20

Light Source

LED built in

LED Type

COB

LED Brand

Bridgelux

Gear

Gear Type

Led Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Power(Watts)

3,5-6,3W

Power Factor

0,5

Constant Current
700mA
IP Rating
Safety Class
Dimmable
Housing Material
Brand

Yes
5-9V
IP20

No
Plastic
KEGU

Illumination Data

Colour Temperature
Lumen Output
Light Efficiency
CRI
Beam Angle
Illumination Diagram

3000K
600lm
75lm/W
90
25°


Packing Info

Box Length
Box Width
Box Height
Box Weight
Pcs/Carton
Barcode
HS Code

10,5cm
11cm
15,5cm
0.520kg
24
5291889058915
9405413990

Certification & Warranty

switch to
one light!

one
LIGHT

