

13 Wall & Ceiling LED>The SMD Cylinders Aluminium

12115L/W/W



15W SMD LED ceiling downlight, ideal for residential and commercial illumination.

Complete with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads





Dimensions



Physical Specification

Item Group	13 Wall & Ceiling LED
Family	The SMD Cylinders Aluminium
Order Code	12115L/W/W
Colour	White
Material	Aluminium
Shape	Circular
Height	100mm
Diameter	130mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No


Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	15W
IP Rating	IP40
Light Source	LED built in
Dimmable	No
F Mark	

Fitting	
Input Type	Constant Current
Input Current	300mA
Voltage	45V
Power(Watts)	13,5W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 5630
LED Brand	Samsung

Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	9,5-15W
Power Factor	0,9

Constant Current	Yes
350mA	27-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Brand	XY

Illumination Data

Colour Temperature	3000K
Lumen Output	1280lm
Light Efficiency	85,33lm/W
CRI	80
Beam Angle	90°
Illumination Diagram	

Packing Info

Box Length	14cm
Box Width	14cm
Box Height	11cm
Box Weight	0.558kg
Pcs/Carton	36
Barcode	5291889041474
HS Code	9405409900

Warranty

3 Years

Weee Directive

Yes

switch to
one light!

one
LIGHT

