

09 Track Lights>The COB Compact Cylinder Range

## 65524T/BBS/W



12W COB track spot with honeycomb.

Complete with 250mA driver.

Complies with standard EN60598-1 and any other specific standards.



### Downloads



### Dimensions



### Related items



40002A/B




40003A/B

### Physical Specification

|            |                                |
|------------|--------------------------------|
| Item Group | 09 Track Lights                |
| Family     | The COB Compact Cylinder Range |
| Order Code | 65524T/BBS/W                   |
| Colour     | Brushed Brass                  |
| Material   | Aluminium                      |
| Shape      | Circular                       |
| Height     | 110mm                          |


|               |              |
|---------------|--------------|
| Diameter      | 55mm         |
| Track mounted | Yes          |
| Indoor        | Yes          |
| Adjustable    | 2 Directions |

#### Electrical Characteristics


| Gear             | Built In  |
|------------------|---|
| Fitting + Driver |   |
| Input Voltage    | 220-240V  |
| 50 Hz            | Yes   |
| 60 Hz            | Yes   |
| Safety Class     |  |
| Power(Watts)     | 12W   |
| IP Rating        | IP20  |
| Light Source     | LED built in  |
| Dimmable         | No  |

| Fitting       |                  |
|---------------|------------------|
| Input Type    | Constant Current |
| Input Current | 250mA            |
| Voltage       | 48V              |
| Power(Watts)  | 12W              |
| IP Rating     | IP20             |
| Light Source  | LED built in     |
| LED Type      | COB              |
| LED Brand     | Sanan            |

| Gear          |            |
|---------------|------------|
| Gear Type     | Led Driver |
| Input Voltage | 220-240V   |

|                  |   |
|------------------|---|
| 50 Hz            | Yes   |
| 60 Hz            | Yes   |
| Power(Watts)     | 12W   |
| Power Factor     | 0,9   |
| Constant Current | Yes   |
| 250mA            | 48  |
| IP Rating        | IP20  |
| Safety Class     |  |
| Dimmable         | No  |
| Housing Material | Plastic   |
| Output Terminal  | Connector   |
| Brand            | Lifud   |
| Protection       | Short Circuit Protection  |

#### Illumination Data

|                      |   |
|----------------------|---|
| Colour Temperature   | 3000K   |
| Lumen Output         | 1080lm  |
| Light Efficiency     | 90lm/W  |
| CRI                  | 90  |
| Beam Angle           | 36°   |
| Illumination Diagram |  |
| Dark Light           | Yes   |

#### Packing Info

|            |               |
|------------|---------------|
| Pcs/Carton | 24            |
| Barcode    | 5291889063407 |
| HS Code    | 9405409900    |

Warranty

5 Years

Weee Directive

Yes

switch to  
**one light!**

one  
LIGHT

