

Product Datasheet

www.1-light.eu

20 Garden & Underwater>LED Path Lights Die cast

67358/AN/W



7W LED Bollard, IP65 for Garden illumination.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



Gallery




Physical Specification

Item Group	20 Garden & Underwater
Family	LED Path Lights Die cast
Order Code	67358/AN/W
Colour	Anthracite
Material	Die Cast
Shape	Rectangular
Length	100mm

Width	50mm
Height	400mm
Surface Floor/Ground	Yes
Outdoor	Yes
Adjustable	No
IK Rating	5
ectrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	7W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	700mA
Voltage	9V
Power(Watts)	6,3W
IP Rating	IP65
Light Source	LED built in
LED Brand	Cree

Gear Type	Led Driver
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	4,8-9,6W
Power Factor	0,9
Constant Current	Yes
700mA	6-12V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Protection	Short Circuit
Ilumination Data	
Ilumination Data Colour Temperature	3000K
	3000K 262lm
Colour Temperature	
Colour Temperature Lumen Output	262lm
Colour Temperature Lumen Output Light Efficiency	262lm 37,42lm/W
Colour Temperature Lumen Output Light Efficiency CRI	262lm 37,42lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	262lm 37,42lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	262lm 37,42lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	262lm 37,42lm/W 80 49°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	262lm 37,42lm/W 80 49° 1 43,5cm
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width	262lm 37,42lm/W 80 49° 43,5cm 8cm
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width Box Height	262lm 37,42lm/W 80 49° 43,5cm 8cm 13cm
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width Box Height Box Weight	262lm 37,42lm/W 80 49° 43,5cm 8cm
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width Box Height	262lm 37,42lm/W 80 49° 43,5cm 8cm 13cm

Energy Label



Certification & Warranty

Warranty 2 Years

Weee Directive Yes

switch to one light!

