

20 Garden & Underwater>The LED Bollards Range Cone reflector

67410A/AN/C



20W LED Bollard, IP65 for Garden illumination.

Supplied with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

Item Group	20 Garden & Underwater
Family	The LED Bollards Range Cone reflector
Order Code	67410A/AN/C
Colour	Anthracite
Material	Die Cast
Diffuser Material	PC
Shape	Circular
Height	1000mm
Diameter	160mm
Surface Floor/Ground	Yes
Outdoor	Yes
Adjustable	No

IK Rating

8

Electrical Characteristics

Gear

Built In

Fitting + Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Safety Class



Power(Watts)

20W

IP Rating

IP65

Light Source

LED built in

Dimmable

No

F Mark



Fitting

Input Type

Constant Current

Input Current

500mA

Voltage

40V

Power(Watts)

20W

IP Rating

IP65

Light Source

LED built in

LED Type

SMD 2835

LED Brand

Osram

Gear

Gear Type

Led Driver

Input Voltage


220-240V

50 Hz


Yes

60 Hz

Yes

Power(Watts)	13,5-20W
Power Factor	0,9
Constant Current	Yes
500mA	27-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	55°C
Operating Temp	85°C
Housing Material	Plastic
Output Terminal	Connector
Protection	Short Circuit

Illumination Data

Colour Temperature	4000K
Lumen Output	1600lm
Light Efficiency	80lm/W
CRI	80
Illumination Diagram	

Packing Info

Box Weight	5.900kg
Pcs/Carton	2
Barcode	5291889051657
HS Code	9405413990

Certification & Warranty

Warranty

2 years

Weee Directive

Yes

switch to
one light!

one
LIGHT

