

20 Garden & Underwater>The Cage Light Bollards Die cast

67504A/AN/C



22W LED Bollard, IP65 for Garden illumination.

Supplied with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

| | |
|----------------------|----------------------------------|
| Item Group | 20 Garden & Underwater |
| Family | The Cage Light Bollards Die cast |
| Order Code | 67504A/AN/C |
| Colour | Anthracite |
| Material | Die Cast |
| Shape | Rectangular |
| Length | 160mm |
| Width | 160mm |
| Height | 900mm |
| Surface Floor/Ground | Yes |
| Outdoor | Yes |
| Adjustable | No |

IK Rating

10

Electrical Characteristics

Gear

Built In

Fitting + Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Safety Class



Power(Watts)

22W

IP Rating

IP65

Light Source

LED built in

Dimmable

No

F Mark



Fitting

Input Type

Constant Current

Input Current

500mA

Voltage

39,31V

Power(Watts)

19,66W

IP Rating

IP65

Light Source

LED built in

LED Type

SMD 2835

LED Brand

Edison

Gear

Gear Type

Led Driver

Input Voltage


220-240V

50 Hz


Yes

60 Hz

Yes

| | |
|------------------|---|
| Power(Watts) | 13,5-20W |
| Power Factor | 0,9 |
| Constant Current | Yes |
| 500mA | 27-40V |
| IP Rating | IP20 |
| Safety Class |  |
| Dimmable | No |
| Ambient Temp | 55°C |
| Operating Temp | 85°C |
| Housing Material | Plastic |
| Output Terminal | Connector |
| Brand | HEP |
| Protection | Short Circuit |

Illumination Data

| | |
|----------------------|---|
| Colour Temperature | 4000K |
| Lumen Output | 1900lm |
| Light Efficiency | 86,36lm/W |
| CRI | 80 |
| Illumination Diagram |  |

Packing Info

| | |
|------------|---------------|
| Box Weight | 6.300kg |
| Pcs/Carton | 1 |
| Barcode | 5291889069317 |
| HS Code | 9405413990 |

Certification & Warranty

switch to
one light!

one
LIGHT

