

21 Industrial & Floodlights>The Floodlights

7030/AN/C



8x1W floodlight, IP65.

Supplied with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery





Physical Specification

Item Group	21 Industrial & Floodlights
Family	The Floodlights
Order Code	7030/AN/C
Colour	Anthracite
Material	Die Cast
Shape	Rectangular
Length	158mm


Height	195mm
Surface Ceiling	Yes
Surface Wall	Yes
Surface Floor/Ground	Yes
Indoor	Yes
Outdoor	Yes
Adjustable	2 Directions

Electrical Characteristics


Gear	Built In
Fitting + Driver	
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	8x1W
IP Rating	IP54
Light Source	LED built in
Dimmable	No
F Mark	

Fitting	
Input Type	Constant Current
Input Current	350mA
Voltage	20V
Power(Watts)	7W
IP Rating	IP54

Gear	
Gear Type	Led Driver

Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	6,3-11,5W
Power Factor	0,95
Constant Current	Yes
350mA	18-33V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	-20 ~ 50°C
Operating Temp	75°C
Housing Material	Plastic
Output Terminal	Connector

Illumination Data

Colour Temperature	4000K
Lumen Output	600lm
Light Efficiency	75lm/W
Beam Angle	20°
Illumination Diagram	

Packing Info

Box Weight	1.267kg
Pcs/Carton	12
Barcode	5291889030393
HS Code	9405413990

Certification & Warranty

switch to
one light!

one
LIGHT

