

INSTALLATION MANUAL


7820A/RGB

ecostrip



100-240V / 12V DC | SMD 5050 | 30LEDs/m | 2W/m/colour | IP20

Set of LED strip + remote. Supplied in 5m roll with double face adhesive tape.



one
LIGHT

A. CUT:


The LED strip can be cut every 10cm (3-LED segment) at the clearly marked positions. Cut carefully at the desired length by using a sharp pair of scissors.

B. CONNECT:


Connect the LED strip to the controller. Ensure that the polarity is correct.

C. INSTALLATION:

Remove the 3M double face adhesive tape from the LED strip gradually during installation and fix into the required position.



D. REMOTE CONTROL



Warnings:

1. The mounting surface must be clean, dry and free from dust or grease.
2. Make sure that the product is installed properly before connecting to electricity.
3. Do not bend, fold or twist the LED strip.
4. Do not bend to install in corners.
5. Do not put excessive pressure on surface of LED strip.
6. Do not cover LED strip with any materials.
7. Do not install in ambient temperatures below -10°C or exceeding 45°C.
8. Always handle the LED strip with care.
9. The LED strip should not be exposed to direct sunlight.
10. LED strips with different batch numbers may have slight variations in colour consistency (CCT±150K).
11. Maintenance and installation should only be carried out by a professional electrician.