

02 Recessed Spots Fixed LED>The Trimless Mini Range Aluminium

## 10112BTR/BS/W



12W COB LED 2-Step trimless Recessed spot, IP20, for general application. Requires 700mA constant current driver.


Complies with standard EN60598-1 and any other specific standards.



### Downloads



### Dimensions



### Gallery



### Must be ordered separately



89015A

Related items



89015AT


Physical Specification

Item Group	02 Recessed Spots Fixed LED
Family	The Trimless Mini Range Aluminium
Order Code	10112BTR/BS/W
Colour	Brass Reflector
Material	Aluminium
Shape	Circular
Height	92mm
Diameter	64mm
Cutout Hole Diameter	70mm
Recessed trimless ceiling	Yes
Depth Required	110mm
Indoor	Yes
Adjustable	No

Electrical Characteristics


Fitting	
Input Type	Constant Current
Input Current	700mA
Safety Class	III
Power(Watts)	12W
IP Rating	IP20
Light Source	LED built in
LED Type	COB

LED Brand	
Cable Length	
F Mark	

Bridgelux
40cm


#### Illumination Data

Colour Temperature	
Lumen Output	
Light Efficiency	
CRI	
Beam Angle	
Illumination Diagram	
Dark Light	

3000K
1100lm
91,67lm/W
90
40°

Yes

#### Packing Info

Pcs/Carton	
Barcode	
HS Code	

48
5291889070078
9405409900

#### Certification & Warranty

Warranty	
Weee Directive	

5 Years
Yes

switch to  
**one light!**

**one**  
LIGHT

