

02 Recessed Spots Fixed LED>Floating Ring Range

10112R/W/W



12W Dark Light COB LED recessed spot with interchangeable ring.

Ring must be ordered separately.

Requires 700mA driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery



Must be ordered separately



050162/B



050162/DC



050162/W



89015A

Related items



89015AT

Physical Specification

Item Group	02 Recessed Spots Fixed LED
Family	Floating Ring Range
Order Code	10112R/W/W
Colour	White
Material	Die Cast
Shape	Circular
Height	97mm
Diameter	85mm
Cutout Hole Diameter	68mm
Recessed Ceiling	Yes
Depth Required	110mm
Indoor	Yes
Outdoor	Yes
Adjustable	No

Electrical Characteristics

Fitting	
Input Type	Constant Current
Input Current	700mA
Safety Class	III
Power(Watts)	12W
IP Rating	IP65
Light Source	LED built in

LED Type
LED Brand
LED Number
Cable Length
F Mark

COB

Bridgelux

1

40cm



Illumination Data

Colour Temperature

3000K

Lumen Output

1100lm

Light Efficiency

91,67lm/W

CRI

90

Beam Angle

50°

Illumination Diagram



Dark Light

Yes

Packing Info

Box Length

9cm

Box Width

9cm

Box Height

8,5cm

Box Weight

0.362kg

Pcs/Carton

50

Barcode

5291889074205

HS Code

9405413990

Certification & Warranty

switch to
one light!

one
LIGHT

