

Product Datasheet

www.1-light.eu

06 Downlights Fixed LED>The 18-30W Round Recessed Panels CCT V

10118FA/B/V



CCT Variable 18W slim downlight LED, IP20, ideal for commercial applications such as offices, galleries and showrooms.

Supplied with 450mA non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



223mm

Gallery



Related items



89024UT

Physical Specification

Item Group

06 Downlights Fixed LED

Family

The 18-30W Round Recessed Panels CCT V

Order Code	10118FA/B/V
Colour	Black
Material	Die Cast
Diffuser Material	Acrylic
Shape	Circular
Height	22mm
Diameter	223mm
Cutout Hole Diameter	210mm
Recessed Ceiling	Yes
Depth Required	50mm
Indoor	Yes
Adjustable	No
Electrical Characteristics	
Gear	External-Included
	External-Included
Gear Fitting + Driver	External-Included
	External-Included 220-240V
Fitting + Driver	
Fitting + Driver Input Voltage	220-240V
Fitting + Driver Input Voltage 50 Hz	220-240V Yes
Fitting + Driver Input Voltage 50 Hz 60 Hz	220-240V Yes
Fitting + Driver Input Voltage 50 Hz 60 Hz Safety Class	220-240V Yes Yes
Fitting + Driver Input Voltage 50 Hz 60 Hz Safety Class Power(Watts)	220-240V Yes Yes
Fitting + Driver Input Voltage 50 Hz 60 Hz Safety Class Power(Watts) IP Rating	220-240V Yes Yes IP20
Fitting + Driver Input Voltage 50 Hz 60 Hz Safety Class Power(Watts) IP Rating Light Source	220-240V Yes Yes IBW IP20 LED built in
Fitting + Driver Input Voltage 50 Hz 60 Hz Safety Class Power(Watts) IP Rating Light Source Dimmable	220-240V Yes Yes ID 18W IP20 LED built in
Fitting + Driver Input Voltage 50 Hz 60 Hz Safety Class Power(Watts) IP Rating Light Source Dimmable	220-240V Yes Yes ID 18W IP20 LED built in
Fitting + Driver Input Voltage 50 Hz 60 Hz Safety Class Power(Watts) IP Rating Light Source Dimmable F Mark	220-240V Yes Yes ID 18W IP20 LED built in
Fitting + Driver Input Voltage 50 Hz 60 Hz Safety Class Power(Watts) IP Rating Light Source Dimmable F Mark	220-240V Yes Yes 18W IP20 LED built in No F

IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Epistar
LED Number	144
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	11,25-18W
Power Factor	0,9
Constant Current	Yes
450mA	25-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	50°C
Operating Temp	75°C
Housing Material	Plastic
Brand	Lifud
Illumination Data	
Colour Temperature	3000K-4000K-5700K
Lumen Output	1800lm
Light Efficiency	100lm/W
CRI	80
Beam Angle	120°
Illumination Diagram	

Pcs/Carton 16 Barcode 5291889078944 HS Code 9405119090

Certification & Warranty	
Warranty	3 years
Weee Directive	Yes



Packing Info

