

Product Datasheet

www.1-light.eu

06 Downlights Fixed LED>UGR19 Office Range

10124U/W/C



24W SMD LED UGR19 downlight, IP44.

Complete with 500mA driver.

Complies with standard EN60598-1 and any other specific standards.





Gallery



Physical Specification

Item Group

06 Downlights Fixed LED

	\mathbf{n}	IIV
– – –		1117
-		
		,

UGR19 Office Range

Order Code	10124U/W/C
Colour	White
Material	Die Cast
Shape	Circular
Height	35mm



Diameter	170mm
Cutout Hole Diameter	160mm
Recessed Ceiling	Yes
Depth Required	55mm
Indoor	Yes
Adjustable	No
IK Rating	4

Electrical Characteristics

Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	24W
IP Rating	IP44
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	

Input Type	Constant Current
Input Current	500mA

Voltage	40V
Safety Class	
Power(Watts)	20W
IP Rating	IP44
Light Source	LED built in
LED Type	SMD 2835



LED Brand

F Mark

Epistar

F

Ge	ar

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	12,5-20W
Power Factor	0,9
Constant Current	Yes
500mA	25-40V
IP Rating	IP44
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	Lifud
Protection	Short Circuit and Overload

Illumination Data

Colour Temperature	4000K
Lumen Output	1800lm
Light Efficiency	75lm/W
CRI	80

Illumination Diagram	
UGR	19

Packing Info

Pcs/Carton

20



Barcode

HS Code

5291889065364

9405409900

Certification & Warranty 3 Years Warranty 3 Years Average Lifetime 30000hrs Weee Directive Yes

switch to one light!



