



Product Datasheet

06 Downlights Fixed LED>The COB Pro Range

10130C/G/W



30W COB LED recessed downlight, IP20.

Complete with 850mA driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



Physical Specification

Item Group	06 Downlights Fixed LED
Family	The COB Pro Range
Order Code	10130C/G/W
Colour	Grey
Material	Aluminium
Shape	Circular
Height	70mm
Diameter	230mm
Cutout Hole Diameter	210mm
Recessed Ceiling	Yes
Depth Required	120mm
Indoor	Yes

Electrical Characteristics

Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	30W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	850mA
Voltage	33V
Safety Class	<u></u>
Power(Watts)	28W
IP Rating	IP20
Light Source	LED built in
LED Type	СОВ
LED Brand	Epistar
F Mark	F
Gear	
Gear Type	Led Driver
Input Voltage	220-240V

50 Hz	Yes
60 Hz	Yes
Power(Watts)	20,4-41,6W
Power Factor	0,9
Constant Current	Yes
850mA	24-49V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	Lifud
Ilumination Data	
Colour Temperature	3000K
Lumen Output	2200lm
Light Efficiency	73,33lm/W
CRI	80
Beam Angle	80°
Illumination Diagram	
Packing Info	
Box Length	26cm
Box Width	26cm
Box Height	9,5cm
Box Weight	1.144kg
Pcs/Carton	9
Barcode	5291889040248
HS Code	9405413990

Warranty 2 years

switch to one light!

