

07 Downlights Adjustable LED>The Zoomable Pop Up Range

## 11128G/B/W



25W COB LED zoomable 15°-45° adjustable downlight with removable honeycomb.

Supplied with 600mA driver.

Complies with standard EN60598-1 and any other specific standards.



### Downloads



### Dimensions



### Gallery






### Physical Specification

Item Group	07 Downlights Adjustable LED
Family	The Zoomable Pop Up Range
Order Code	11128G/B/W
Colour	Black
Material	Aluminium
Shape	Circular
Height	58mm


Diameter	134mm
Cutout Hole Diameter	120mm
Recessed Ceiling	Yes
Depth Required	70mm
Indoor	Yes
Adjustable	2 Directions

## Electrical Characteristics

Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	25W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	

Fitting	
Input Type	Constant Current
Input Current	600mA
Safety Class	
IP Rating	IP20
Light Source	LED built in
LED Type	COB
LED Brand	Bridgelux
LED Number	1

## Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	18-26,4W
Power Factor	0,95
Constant Current	Yes
600mA	30-44V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	KGP
Protection	Short Circuit Protection,Overload Protection,No-load Protection

## Illumination Data

Colour Temperature	3000K
Lumen Output	2500lm
Light Efficiency	100lm/W
CRI	90
Beam Angle	15°-45°
Illumination Diagram	

## Packing Info

Box Weight	0.894kg
Pcs/Carton	18
Barcode	5291889076476
HS Code	9405413990

Warranty

5 years

switch to  
**one light!**

one  
LIGHT

