

04 Recessed Spots Adjustable LED>The 6,5W COB Recessed Cylinders

11207C/W/W



2x6,5W COB LED recessed adjustable spot, for general lighting applications.

Requires 2x700mA constant current LED drivers.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Must be ordered separately



89008A



89008AT



Physical Specification

Item Group	04 Recessed Spots Adjustable LED
Family	The 6,5W COB Recessed Cylinders
Order Code	11207C/W/W
Colour	White
Material	Die Cast
Shape	Rectangular

Length	168mm
Width	90mm
Height	85mm
Cutout Hole Diameter	2x83mm
Recessed Ceiling	Yes
Depth Required	90mm
Indoor	Yes
Adjustable	2 Directions

Electrical Characteristics

Fitting

Input Type	Constant Current
Input Current	700mA
Voltage	9,3V
Safety Class	
Power(Watts)	2x6,5W
IP Rating	IP20
Light Source	LED built in
LED Type	COB
LED Brand	Bridgelux
LED Number	1
Cable Length	40cm
F Mark	

Illumination Data

Colour Temperature	3000K
Lumen Output	2x550lm
Light Efficiency	84lm/W
CRI	90

Beam Angle

36°

Illumination Diagram



Dark Light

Yes

Packing Info

Box Length

17,5cm

Box Width

9,5cm

Box Height

10cm

Box Weight

0.558kg

Pcs/Carton

24

Barcode

5291889058410

HS Code

9405413990

Certification & Warranty

Warranty

5 years

switch to
one light!

one
LIGHT

