

13 Wall & Ceiling LED>LED Decorative Cylinders

12112T/B/W



12W COB LED adjustable ceiling light.

Complete with black and brass reflectors.

Supplied with 350mA driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery



Physical Specification

Item Group

13 Wall & Ceiling LED

Family

LED Decorative Cylinders

Order Code

12112T/B/W

Colour

Black

Material

Aluminium

Shape



Circular


Height

95mm


Diameter	80mm
Recessed Ceiling	Yes
Indoor	Yes
Adjustable	2 Directions

Electrical Characteristics


Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	12W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	

Fitting	
Input Type	Constant Current
Input Current	350mA
Safety Class	
IP Rating	IP20
Light Source	LED built in
LED Type	COB
LED Brand	Bridgelux
LED Number	1

Gear	
Gear Type	Led Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	6,5-9,5W
Power Factor	0,9
Constant Current	Yes
350mA	27-38V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	KEGU
Protection	Short Circuit Protection,Overload Protection,No-load Protection

Illumination Data

Colour Temperature	3000K
Lumen Output	1080lm
Light Efficiency	90lm/W
CRI	90
Beam Angle	36°
Illumination Diagram	
Dark Light	Yes

Packing Info

Box Weight	0.505kg
Pcs/Carton	20
Barcode	5291889076513
HS Code	9405413990

Warranty

5 years

switch to
one light!

one
LIGHT

