

13 Wall & Ceiling LED>LED Decorative Cylinders

12112T/W/W



12W COB LED adjustable ceiling light.

Complete with black and brass reflectors.

Supplied with 350mA driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

Item Group	13 Wall & Ceiling LED
Family	LED Decorative Cylinders
Order Code	12112T/W/W
Colour	White
Material	Aluminium
Shape	Circular
Height	95mm
Diameter	80mm
Recessed Ceiling	Yes
Indoor	Yes
Adjustable	2 Directions

Gear

Built In

Fitting + Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Safety Class



Power(Watts)

12W

IP Rating

IP20

Light Source

LED built in

Dimmable

No

F Mark



Fitting

Input Type

Constant Current

Input Current

350mA

Safety Class



IP Rating

IP20

Light Source

LED built in

LED Type

COB

LED Brand

Bridgelux

LED Number

1

Gear

Gear Type

Led Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz


Yes

Power(Watts)


6,5-9,5W

Power Factor

0,9

Constant Current	Yes
350mA	27-38V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	KEGU
Protection	Short Circuit Protection,Overload Protection,No-load Protection

Illumination Data

Colour Temperature	3000K
Lumen Output	1080lm
Light Efficiency	90lm/W
CRI	90
Beam Angle	36°
Illumination Diagram	
Dark Light	Yes

Packing Info

Box Weight	0.505kg
Pcs/Carton	20
Barcode	5291889076520
HS Code	9405413990

Certification & Warranty

switch to
one light!

one
LIGHT

