

Product Datasheet

www.1-light.eu

08 Strips & Profiles>24V Linkable Modules Aluminium

38001A/W



1W LED Linkable module, IP20 .

Requires 24V DC constant voltage LED driver.

Complies with standard EN60598-1 and any other specific standards.



| Downloads | Dimensions | |
|-----------|-----------------------|--|
| °O CE | l 100mm l 12mm | |

Accessories



38006A



38006A



38007A



38007A

Physical Specification

| Item Group | 08 Strips & Profiles |
|------------|--------------------------------|
| Family | 24V Linkable Modules Aluminium |
| Order Code | 38001A/W |
| Material | Aluminium |
| Shape | Rectangular |
| Length | 100mm |



| Width | 12mm |
|-----------------|------|
| Height | 5m |
| Surface Ceiling | Yes |
| Surface Wall | Yes |
| Indoor | Yes |

Electrical Characteristics

| Fitting | |
|---------------|------------------|
| Input Type | Constant Voltage |
| Input Voltage | 24V DC |
| Safety Class | |
| Power(Watts) | 1 VV |
| IP Rating | IP20 |
| Light Source | LED built in |
| LED Type | SMD |
| F Mark | F |
| | |

Illumination Data

| Colour Temperature | 3000K |
|----------------------|--------|
| Lumen Output | 60lm |
| Light Efficiency | 60lm/W |
| Illumination Diagram | |

| Pcs/Carton | 100 |
|------------|---------------|
| Barcode | 5291889017004 |
| HS Code | 9405104090 |



| Warranty | 3 Years |
|----------------|---------|
| Weee Directive | Yes |

switch to one light!

Certification & Warranty



