

Product Datasheet

www.1-light.eu

08 Strips & Profiles>24V Linkable Modules Aluminium

38002A/BL



3W LED Linkable module, IP20.

Requires 24V DC constant voltage LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads





Dimensions



Accessories







38006B



38007B



38007B

Physical Specification

| Item Group | 08 Strips & Profiles |
|------------|--------------------------------|
| Family | 24V Linkable Modules Aluminium |
| Order Code | 38002A/BL |
| Material | Aluminium |
| Shape | Rectangular |
| Length | 200mm |

| Width | 12mm |
|----------------------------|------------------|
| Surface Ceiling | Yes |
| Surface Wall | Yes |
| Indoor | Yes |
| | |
| Electrical Characteristics | |
| | |
| | |
| Fitting | |
| Input Type | Constant Voltage |
| Input Voltage | 24V DC |
| Safety Class | |
| Power(Watts) | 3W |
| IP Rating | IP20 |
| Light Source | LED built in |
| LED Type | SMD |
| F Mark | F |
| | |
| llumination Data | |
| | |
| Colour Temperature | Blue |
| Illumination Diagram | |
| | |
| Packing Info | |
| Dec/Conten | 100 |
| Pcs/Carton | 100 |
| Barcode | 5291889017042 |
| HS Code | 9405104090 |

Certification & Warranty

| Warranty | 3 Years |
|----------------|---------|
| Weee Directive | Yes |



