

New 2025 Edition 2>Office & Kitchen

38151A/W/V



CCT and Power variable 50W UGR19 Linear system with diffuser for surface or suspended installation, ideal for offices.

Complete with power variable driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery



Accessories




050170




050170C/W

Related items



050170D/W/V





38150E/W

Physical Specification

Item Group	New 2025 Edition 2
Family	Office & Kitchen
Order Code	38151A/W/V
Colour	White
Material	Aluminium
Shape	Rectangular
Length	1500mm
Width	70mm
Height	35mm
Surface Ceiling	Yes
Suspended Ceiling	Yes
Indoor	Yes
Adjustable	No

Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	30W-40W-50W
IP Rating	IP20

Light Source	LED built in
Dimmable	No
Cable Length	300cm
F Mark	


Fitting

Input Type	Constant Current
IP Rating	IP20
Light Source	LED built in
LED Type	SMD

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
IP Rating	IP20
Dimmable	No
Protection	0

Illumination Data

Colour Temperature	3000K-4000K-5000K
Lumen Output	4250lm (50W)
Light Efficiency	85lm/W
CRI	90
Illumination Diagram	
UGR	19

Packing Info

Pcs/Carton	9
------------	---

Warranty

3 Years

Weee Directive

Yes

switch to
one light!

one
LIGHT

