

Product Datasheet

www.1-light.eu

21 Industrial & Floodlights>The Supermarket LED Linear Range Aluminium

38280/B/C



80W adjustable supermarket linear light.

Complete with 2 Fixing clips, 2 Connectors & 2 Suspension kits.

Complies with standard EN60598-1 and any other specific standards.



Downloads










Dimensions



1	1200mm	1
000000		140mm

Gallery





Physical Specification

Item Group	21 Industrial & Floodlights
Family	The Supermarket LED Linear Range Aluminium
Order Code	38280/B/C
Colour	Black
Material	Aluminium
Shape	Rectangular
Length	1200mm

Width	140mm
Height	50mm
Surface Ceiling	Yes
Suspended Ceiling	Yes
Indoor	Yes
Adjustable	1 Direction
Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	80W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	600mA+1500mA
Safety Class	
Power(Watts)	80W

Safety Class	
Power(Watts)	80W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 3030/2835
LED Brand	Epistar

Gear Type	Led Driver
Input Voltage	220-240V
Power(Watts)	16,8-22,8W & 42-60W
Power Factor	0,95
Constant Current	Yes
600mA	28-38V
1500mA	28-40V
IP Rating	IP20
Brand	BOKE

0

Illumination Data

Protection

Colour Temperature	4000K
Lumen Output	7400lm
Light Efficiency	92,5lm/W
CRI	90
Illumination Diagram	

Packing Info

Box Weight	5.075kg
Pcs/Carton	4
Barcode	5291889072904
HS Code	9405413990

Certification & Warranty

switch to one light!

