

06 Downlights Fixed LED>UGR19 Office Range

## 50115UV/W/V



15W SMD LED UGR19 downlight with adjustable CCT, IP44.

Complete with 350mA driver.

Complies with standard EN60598-1 and any other specific standards.




### Downloads



### Dimensions



### Gallery






### Physical Specification

Item Group	06 Downlights Fixed LED
Family	UGR19 Office Range
Order Code	50115UV/W/V
Colour	White
Material	Die Cast
Shape	Rectangular
Length	145mm

Width	145mm
Height	33mm
Cutout Hole Width	130mm
Cutout Hole Length	130mm
Recessed Ceiling	Yes
Depth Required	70mm
Indoor	Yes
Adjustable	No


## Electrical Characteristics

Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	15W
IP Rating	IP44
Light Source	LED built in
Dimmable	No
F Mark	


Fitting	
Input Type	Constant Current
Input Current	350mA
Voltage	38,5V
Safety Class	
Power(Watts)	13,47W
IP Rating	IP44
Light Source	LED built in

LED Type	SMD 2835
LED Brand	Epistar
F Mark	

## Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	8,75-14W
Power Factor	0,9
Constant Current	Yes
350mA	25-40V
IP Rating	IP44
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	Lifud
Protection	Short Circuit and Overload

## Illumination Data

Colour Temperature	3000K-4000K-6000K
Lumen Output	1650lm
Light Efficiency	110lm/W
CRI	80
Illumination Diagram	
UGR	19

## Packing Info

Box Weight	0.535kg
Pcs/Carton	20
Barcode	5291889075189
HS Code	9405413990

#### Certification & Warranty

Warranty	3 years
----------	---------

switch to  
**one light!**

one  
LIGHT

