



# **Product Datasheet**

### 06 Downlights Fixed LED>Shop Square Boxes

## 50130B/W/W



30W downlight LED, shop square boxes range IP20, ideal for commercial applications such as offices, galleries and showrooms.

Supplied with 750mA non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads










#### Dimensions



#### **Physical Specification**

Item Group	06 Downlights Fixed LED
Family	Shop Square Boxes
Order Code	50130B/W/W
Colour	White
Material	Aluminium
Shape	Rectangular
Length	140mm
Width	140mm
Height	114mm
Cutout Hole Width	130mm
Cutout Hole Length	130mm
Recessed Ceiling	Yes

Depth Required	120mm
Indoor	Yes
Adjustable	No
Electrical Characteristics	
Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	30W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	750mA
Voltage	35,5V
Safety Class	
Power(Watts)	26,62W
IP Rating	IP20
Light Source	LED built in
LED Type	COB
LED Brand	Sanan
Gear	
Gear Type	Led Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	25-30W
Power Factor	0,9
Constant Current	Yes
750mA	33-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Brand	Lifud
Ilumination Data	
Colour Temperature	3000K
Lumen Output	2600lm
Lumen Output  Light Efficiency	2600lm 86,67lm/W
Light Efficiency	86,67lm/W
Light Efficiency CRI	86,67lm/W 80
Light Efficiency  CRI  Beam Angle	86,67lm/W 80
Light Efficiency  CRI  Beam Angle	86,67lm/W 80
Light Efficiency  CRI  Beam Angle  Illumination Diagram	86,67lm/W 80 30°
Light Efficiency  CRI  Beam Angle  Illumination Diagram	86,67lm/W 80
Light Efficiency  CRI  Beam Angle  Illumination Diagram	86,67lm/W 80 30°
Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length	86,67lm/W 80 30°  16cm
Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length  Box Width	86,67lm/W 80 30°  16cm
Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height	86,67lm/W 80 30°  16cm 16cm
Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height  Pcs/Carton	86,67lm/W 80 30° 16cm 13cm

#### Certification & Warranty

Warranty	3 Years
Weee Directive	Yes



