

Product Datasheet

New 2025 Edition 2>Downlights Fixed LED

50140BW/W/V



60x60 backlit IP65 recessed CCT Variable LED panel for T-rail false ceilings. Can be recessed or suspended. Uniform lighting, ideal for commercial applications.

Complete with 950mA driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads	Dimensions
	595mm I

Related items





050017

050108

Physical Specification

Item Group

New 2025 Edition 2

_	\sim	\sim 1	1. 7
_	~	mı	IV
	a		I Y
			,

Downlights Fixed LED

Order Code	50140BW/W/V
Colour	White
Material	Aluminium + Steel
Shape	Rectangular
Length	595mm



Width	595mm
Height	35mm
Recessed T-Ceiling	Yes
Depth Required	60mm
Indoor	Yes
Adjustable	No

Electrical Characteristics

Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	40W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current

Input Current

Safety Class

950mA

IP65
LED built in
SMD 2835
Led Driver



Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Constant Current	Yes
IP Rating	IP65
Safety Class	
Dimmable	No
Brand	Yingjiao
Protection	No-Load, Short Circuit

Illumination Data

Colour Temperature	3000K-4000K-5700K
Lumen Output	4000lm
Light Efficiency	100lm/W
CRI	80
Illumination Diagram	

Packing Info	
Box Weight	2.166kg
Pcs/Carton	4
Barcode	5291889077121
HS Code	9405119090



Warranty

switch to one light!



