

06 Downlights Fixed LED>The 48W Square Panels Aluminium

## 50148E/W/W



60x60 recessed LED panel for T-rail false ceilings. Can be recessed or suspended. Uniform lighting, ideal for commercial applications.

Requires 1200mA LED driver.

Complies with standard EN60598-1 and any other specific standards.



### Downloads



### Dimensions



### Must be ordered separately



89048

### Accessories



050017



050108

Related items



89048T



89050L



89050TLD

Physical Specification

Item Group	06 Downlights Fixed LED
Family	The 48W Square Panels Aluminium
Order Code	50148E/W/W
Colour	White
Material	Aluminium
Diffuser Material	Acrylic
Shape	Rectangular
Length	595mm
Width	595mm
Height	20mm
Recessed T-Ceiling	Yes
Depth Required	50mm
Indoor	Yes
Adjustable	No

Electrical Characteristics

Fitting	
Input Type	Constant Current
Input Current	1200mA
Safety Class	III
Power(Watts)	48W
IP Rating	IP20
Light Source	LED built in

LED Type	SMD 2835
LED Brand	Epistar
LED Number	240

#### Illumination Data

Colour Temperature	3000K
Lumen Output	4000lm
Light Efficiency	83,33lm/W
CRI	80
Beam Angle	120°
Illumination Diagram	

#### Packing Info

Box Length	72cm
Box Width	65cm
Box Height	4,5cm
Box Weight	2,7Kg
Pcs/Carton	6
Barcode	5291889041931
HS Code	9405109890

#### Certification & Warranty

Warranty	2 Years
----------	---------

Average Lifetime

30000 hours

Weee Directive

Yes

switch to  
**one light!**

one  
LIGHT

