

14 Plafo>The LED Decorative Plafo Round

## 62130N/AN/W



20W LED Decorative Plafo, IP20, suitable for residential and commercial application.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads






Dimensions




Physical Specification

|                 |                                |
|-----------------|--------------------------------|
| Item Group      | 14 Plafo                       |
| Family          | The LED Decorative Plafo Round |
| Order Code      | 62130N/AN/W                    |
| Colour          | Anthracite                     |
| Material        | Aluminium                      |
| Shape           | Circular                       |
| Height          | 80mm                           |
| Diameter        | 300mm                          |
| Surface Ceiling | Yes                            |
| Indoor          | Yes                            |
| Adjustable      | No                             |


| Gear             | External-Included   |
|------------------|---|
| Fitting + Driver |   |
| Input Voltage    | 220-240V  |
| 50 Hz            | Yes   |
| 60 Hz            | Yes   |
| Safety Class     |    |
| Power(Watts)     | 20W   |
| IP Rating        | IP20  |
| Light Source     | LED built in  |
| Dimmable         | No  |
| F Mark           |  |

| Fitting       |   |
|---------------|---|
| Input Type    | Constant Current  |
| Input Current | 500mA   |
| Voltage       | 38V   |
| Power(Watts)  | 19W   |
| IP Rating     | IP20  |
| Light Source  | LED built in  |
| LED Type      | SMD 2835  |
| LED Brand     | Bridgelux   |
| F Mark        |  |

| Gear          |            |
|---------------|------------|
| Gear Type     | Led Driver |
| Input Voltage | 220-240V   |
| 50 Hz         | Yes        |
| 60 Hz         | Yes        |
| Power(Watts)  | 13,5-21W   |

|                  |   |
|------------------|---|
| Power Factor     | 0,9   |
| Constant Current | Yes   |
| 500mA            | 27-42V  |
| IP Rating        | IP20  |
| Safety Class     |  |
| Dimmable         | No  |
| Housing Material | Plastic   |
| Output Terminal  | Cable   |
| Brand            | Kegu  |

### Illumination Data

|                      |   |
|----------------------|---|
| Colour Temperature   | 3000K   |
| Lumen Output         | 1700lm  |
| Light Efficiency     | 85lm/W  |
| CRI                  | 80  |
| Illumination Diagram |  |

### Packing Info

|               |               |
|---------------|---------------|
| Box Length    | 40cm          |
| Box Width     | 40cm          |
| Box Height    | 14cm          |
| Box Weight    | 1.300kg       |
| Pcs/Carton    | 1             |
| Carton Length | 40cm          |
| Carton Width  | 40cm          |
| Carton Height | 14cm          |
| Carton Weight | 1,3Kg         |
| Barcode       | 5291889056812 |
| HS Code       | 9405409900    |

Warranty

3 Years

Weee Directive

Yes

switch to  
**one light!**

one  
LIGHT

