



# **Product Datasheet**

## 14 Plafo>LED Die Cast Panel Range

# 62140F/W/C



40W LED slim plafo light, IP40, suitable for residential and commercial application.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









#### Dimensions



#### Gallery



#### **Physical Specification**

14 Plafo
LED Die Cast Panel Range
62140F/W/C
White
Die Cast
Circular
47mm

Diameter	420mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No
lectrical Characteristics	
Coor	External Included
Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	40W
IP Rating	IP40
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	1000mA
Voltage	38V
Safety Class	<u> </u>
Power(Watts)	38W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 4014
LED Brand	Zhaochi

F Mark

F

Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	34-39W
Power Factor	0,9
Constant Current	Yes
1000mA	34-39V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	40°C
Operating Temp	80°C
Housing Material	Plastic
Output Terminal	Cable
Fast Connector	Yes
Fast Connector Type	Other
Brand	KEGU
Illumination Data	
Colour Toron another	400016
Colour Temperature	4000K
Light Efficiency	2800lm
Light Efficiency	70lm/W
CRI	80
Illumination Diagram	
Packing Info	
Box Length	46cm
Box Width	46cm

Box Height	7cm
Box Weight	3.540kg
Pcs/Carton	5
Barcode	5291889040712
HS Code	9405413990

### Certification & Warranty

Warranty	2 Years
Weee Directive	Yes



