



Product Datasheet

14 Plafo>The Ultra Slim LED Plafo Aluminium

62160FB/B/C



60W LED slim plafo light, IP20, suitable for residential and commercial application.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads










Dimensions



Physical Specification

Item Group	14 Plafo
Family	The Ultra Slim LED Plafo Aluminium
Order Code	62160FB/B/C
Colour	Black
Material	Aluminium
Shape	Circular
Height	43mm
Diameter	585mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No

Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	60W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	1500mA
Voltage	39V
Safety Class	
Power(Watts)	58,5W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Sanan
F Mark	F
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes

Power(Watts)	37,5-63W
Power Factor	0,9
Constant Current	Yes
1500mA	25-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	40°C
Operating Temp	80°C
Housing Material	Plastic
Output Terminal	Cable
Fast Connector	Yes
Fast Connector Type	Other
Brand	Lifud
umination Data	
umination Data Colour Temperature	4000K
	4000K 5300lm
Colour Temperature	
Colour Temperature Lumen Output	5300lm
Colour Temperature Lumen Output Light Efficiency	5300lm 88,33lm/W
Colour Temperature Lumen Output Light Efficiency CRI	5300lm 88,33lm/W
Colour Temperature Lumen Output Light Efficiency CRI	5300lm 88,33lm/W
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram	5300lm 88,33lm/W
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram	5300lm 88,33lm/W
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram acking Info	5300lm 88,33lm/W 90
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram acking Info Box Weight	5300lm 88,33lm/VV 90 5.100kg
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram acking Info Box Weight Pcs/Carton	5300lm 88,33lm/W 90 5.100kg

Certification & Warranty

switch to one light!

