

Product Datasheet

16 Decorative>LED Pendant Rings

62180NB/B/W



80W LED Pendant , IP20 suitable for residential and commercial application .

Complete with 1000mA drivers.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions

1500mm	
l 780mm l	

Physical Specification

Item Group	16 Decorative
Family	LED Pendant Rings
Order Code	62180NB/B/W
Colour	Black
Material	Aluminium
Shape	Circular
Height	1500mm

Diameter	780mm
Suspended Ceiling	Yes
Indoor	Yes
Adjustable	No



Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	80W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F

Fitting

Input Type	Constant Current
Input Current	1000mA
Voltage	2x38V
Power(Watts)	2x38W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Epistar
F Mark	F

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	27-42W



Power Factor	0,9
Constant Current	Yes
1000mA	27-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	Lifud

Illumination Data

Colour Temperature	3000K
Lumen Output	5600lm
Light Efficiency	70lm/W
CRI	80
Illumination Diagram	

Packing Info

Box Weight	8.300kg
Pcs/Carton	1
Barcode	5291889062769
HS Code	9405413990



Warranty

2 years

switch to one light!



