



Product Datasheet

16 Decorative>LED Pendant Rings

62180NB/W/W



80W LED Pendant, IP20 suitable for residential and commercial application.

Complete with 1000mA drivers.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



Physical Specification

Item Group	16 Decorative
Family	LED Pendant Rings
Order Code	62180NB/W/W
Colour	White
Material	Aluminium
Shape	Circular
Height	1500mm
Diameter	780mm
Suspended Ceiling	Yes
Indoor	Yes
Adjustable	No

Gear Type

Input Voltage

Power(Watts)

50 Hz

60 Hz

Power Factor	0,9
Constant Current	Yes
1000mA	27-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	Lifud
Illumination Data	
Colour Temperature	3000K
Colour Temperature Lumen Output	3000K 5600lm
Lumen Output	5600lm
Lumen Output Light Efficiency	5600lm 70lm/W
Lumen Output Light Efficiency CRI	5600lm 70lm/W 80
Lumen Output Light Efficiency CRI	5600lm 70lm/W 80
Lumen Output Light Efficiency CRI Illumination Diagram	5600lm 70lm/W 80
Lumen Output Light Efficiency CRI Illumination Diagram	5600lm 70lm/W 80
Lumen Output Light Efficiency CRI Illumination Diagram Packing Info	5600lm 70lm/W 80
Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Weight	5600lm 70lm/VV 80 8.300kg
Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Weight Pcs/Carton	5600lm 70lm/W 80 8.300kg 1

Certification & Warranty

switch to one light!

