

21 Industrial & Floodlights>The Industrial IP65 LED UFO Range Aluminium

63100N/C



100W SMD LED Industrial High Bay, IP65.

Supplied with dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Related items





050114HA

Physical Specification

Item Group	21 Industrial & Floodlights
Family	The Industrial IP65 LED UFO Range Aluminium
Order Code	63100N/C
Colour	Black
Material	Aluminium
Shape	Circular
Height	160mm

Diameter	250mm
Surface Ceiling	Yes
Surface Wall	Yes
Suspended Ceiling	Yes
Indoor	Yes
Outdoor	Yes
Adjustable	No


Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	100W
IP Rating	IP65
Light Source	LED built in
Dimmable	Yes
Dimmer type	1-10V
Cable Length	30cm
F Mark	


Fitting	
Input Type	Constant Current
Input Current	500mA
Voltage	190V
Power(Watts)	95W
IP Rating	IP65
Light Source	LED built in

LED Type	SMD 2835
LED Brand	Osram

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	90-130W
Power Factor	0,9
Constant Current	Yes
500mA	180-260V
IP Rating	IP65
Safety Class	
Brand	Lifud

Illumination Data

Colour Temperature	4000K
Lumen Output	13000lm
Light Efficiency	130lm/W
CRI	80
Beam Angle	90°
Illumination Diagram	

Packing Info

Box Weight	2.500kg
Pcs/Carton	1
Barcode	5291889067948
HS Code	9405413990

Warranty

5 years

switch to
one light!

one
LIGHT

