



Product Datasheet

10 Track Spots>The Track Floodlight Range

65020T/W/W



LED Linear track light, high lumen output ideal for shops and showrooms.

Complete with driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads










Dimensions



Related items



40003A/W

Physical Specification

Item Group	10 Track Spots
Family	The Track Floodlight Range
Order Code	65020T/W/W
Colour	White
Material	Die Cast
Shape	Rectangular
Length	170mm

Width	35mm
Height	105mm
Track mounted	Yes
Indoor	Yes
Adjustable	2 Directions


Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	20W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
Fitting	
Input Type	Constant Current
Input Current	600mA
Voltage	30V
Power(Watts)	20W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 3030
LED Brand	Lumileds
LED Number	20

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	16,2-25,2W
Power Factor	0,9
Constant Current	Yes
600mA	27-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Manufacturer	Lifud
Protection	Short Circuit Protection
Illumination Data	
Colour Temperature	3000K
Colour Temperature Lumen Output	1400lm
Colour Temperature Lumen Output Light Efficiency	1400lm 70lm/W
Colour Temperature Lumen Output Light Efficiency CRI	1400lm 70lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	1400lm 70lm/W
Colour Temperature Lumen Output Light Efficiency CRI	1400lm 70lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	1400lm 70lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	1400lm 70lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	1400lm 70lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	1400lm 70lm/W 80 24°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length	1400lm 70lm/W 80 24° 18cm
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width	1400lm 70lm/W 80 24° 18cm
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width Box Height	1400lm 70lm/W 80 24° 18cm 16cm 4.5cm

Energy Label



Certification & Warranty

Warranty 2 Years

Weee Directive Yes

switch to one light!

