

Product Datasheet

www.1-light.eu

09 Track Lights>The Track Floodlight Range

65040T/W/C



40W COB LED track spot with, ideal for shops and showrooms.

Complete with 1050mA driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



Related items







40003A/W

Physical Specification

Item Group	09 Track Lights
Family	The Track Floodlight Range
Order Code	65040T/W/C
Colour	White
Material	Aluminium
Shape	Rectangular
Length	225mm

Width	110mm
Height	220mm
Track mounted	Yes
Indoor	Yes
Adjustable	2 Directions

Electrical Characteristics

Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	40W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
Fitting	
Input Type	Constant Current
Input Current	1050mA
Voltage	36V
Power(Watts)	37,8W
IP Rating	IP20
Light Source	LED built in
LED Type	СОВ
LED Brand	Sanan
LED Number	1

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	31,5-44,1W
Power Factor	0,9
Constant Current	Yes
1050mA	30-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Brand	Lifud
Illumination Data	
Illumination Data Colour Temperature	4000K
	4000K 3600lm
Colour Temperature	
Colour Temperature Lumen Output	3600lm
Colour Temperature Lumen Output Light Efficiency	3600lm 90lm/W
Colour Temperature Lumen Output Light Efficiency CRI	3600lm 90lm/W 90
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	3600lm 90lm/W 90
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	3600lm 90lm/W 90
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	3600lm 90lm/W 90
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	3600lm 90lm/W 90
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	3600lm 90lm/W 90 60°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Pcs/Carton	3600lm 90lm/W 90 60°

Certification & Warranty

Warranty	3 Years
Weee Directive	Yes



