



Product Datasheet

09 Track Lights>The Cylindrical Track Light

65608T/G/D



3x1W LED track spot with, ideal for shops and showrooms.

Supplied with electronic high frequency control driver as standard.

Complies with standard EN60598-1 and any other specific standards.




Downloads






Dimensions



Related items



40003A/G

Physical Specification

09 Track Lights
The Cylindrical Track Light
65608T/G/D
Grey
Die Cast
Circular
170mm

Diameter	55mm
Track mounted	Yes
Indoor	Yes
Adjustable	2 Directions
Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	3W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
Fitting	

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	3W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
Fitting	
Input Type	Constant Current
Safety Class	
Power(Watts)	
	3W
IP Rating	JP20
IP Rating	IP20
IP Rating	IP20
IP Rating Light Source	IP20
IP Rating Light Source Gear	IP20 LED built in
IP Rating Light Source Gear Gear Type	LED built in Led Driver
IP Rating Light Source Gear Gear Type Input Voltage	LED built in Led Driver 220-240V
IP Rating Light Source Gear Gear Type Input Voltage 50 Hz	LED built in Led Driver 220-240V Yes

Power Factor	0,5
Constant Current	Yes
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Illumination Data	
Colour Tomporatura	6000K
Colour Temperature	6000K
Lumen Output	217lm
Light Efficiency	72,33lm/W
Beam Angle	60°
Illumination Diagram	
Packing Info	
Box Weight	0.717kg
Pcs/Carton Pcs/Carton	30
Barcode	5291889024071
HS Code	9405413990
Certification & Warranty	
Warranty	2 years

switch to one light!

