

## **Product Datasheet**

www.1-light.eu

09 Track Lights>The COB Track Light Range Aluminium

65611T/G/W



15W COB LED track spot with, ideal for shops and showrooms.

Supplied with electronic high frequency control driver as standard.

Complies with standard EN60598-1 and any other specific standards.



Downloads










Dimensions



## Related items



40003A/G

## Physical Specification

Item Group	09 Track Lights
Family	The COB Track Light Range Aluminium
Order Code	65611T/G/W
Colour	Grey
Material	Aluminium
Shape	Circular
Height	105mm

Diameter	72mm
Track mounted	Yes
Indoor	Yes
Adjustable	2 Directions
ectrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	15W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
Fitting	
Input Type	Constant Current
Input Current	350mA
Voltage	38V
Safety Class	
Power(Watts)	13,3W
IP Rating	IP20
Light Source	LED built in
LED Type	СОВ
LED Brand	Sanan
Gear	

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	9,5-14,7W
Power Factor	0,5
Constant Current	Yes
350mA	27-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Brand	Lifud
Protection	Short Circuit Protection
Illumination Data	
Colour Temperature	3000K
	3000K 1100lm
Colour Temperature	
Colour Temperature  Lumen Output	1100lm
Colour Temperature  Lumen Output  Light Efficiency	1100lm 73,33lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI	1100lm 73,33lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	1100lm 73,33lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	1100lm 73,33lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	1100lm 73,33lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	1100lm 73,33lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	1100lm  73,33lm/W  80  36°
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length	1100lm  73,33lm/VV  80  36°  21cm
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length  Box Width	1100lm  73,33lm/W  80  36°  21cm  12,5cm
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height	1100lm  73,33lm/W  80  36°  21cm  12,5cm  8,5cm
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height  Box Weight	1100lm  73,33lm/W  80  36°  21cm  12,5cm  8,5cm  0.675kg

## Certification & Warranty

Warranty 2 years



