



Product Datasheet

09 Track Lights>The COB Zoomable Cylinders

65650BT/W/C



20W adjustable beam 20°-60° track spot with COB LED, ideal for shops and showrooms.

Supplied with electronic high frequency control driver as standard.

Complies with standard EN60598-1 and any other specific standards.









Downloads









Dimensions



Related items







40002A/W



40003A/W

Physical Specification

Item Group	09 Track Lights
Family	The COB Zoomable Cylinders
Order Code	65650BT/W/C
Colour	White
Material	Die Cast
Diffuser Material	Plastic
Shape	Circular

Height	120mm
Diameter	75mm
Track mounted	Yes
Indoor	Yes
Adjustable	2 Directions
lectrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	20W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
Fitting	
Input Type	Constant Current
Input Current	500mA
Safety Class	
IP Rating	IP20
Light Source	LED built in
LED Type	СОВ
LED Brand	Bridgelux
Gear	
Gear Type	Led Driver
Input Voltage	220-240V

50 Hz	Yes
60 Hz	Yes
Constant Current	Yes
500mA	36V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	50°C
Operating Temp	80°C
Housing Material	Plastic
Output Terminal	Connector
Brand	Vossloh-Schwabe
Protection	Short Circuit Protection
Illumination Data	
Illumination Data	
Illumination Data Colour Temperature	4000K
	4000K 2000lm
Colour Temperature	
Colour Temperature Lumen Output	2000lm
Colour Temperature Lumen Output Light Efficiency	2000lm 100lm/W
Colour Temperature Lumen Output Light Efficiency CRI	2000lm 100lm/W 90
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	2000lm 100lm/W 90
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	2000lm 100lm/W 90
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	2000lm 100lm/W 90
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	2000lm 100lm/W 90
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	2000lm 100lm/VV 90 20°-60°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Weight	2000lm 100lm/W 90 20°-60° 0.726kg
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Weight Pcs/Carton	2000lm 100lm/W 90 20°-60° 0.726kg

Certification & Warranty

Warranty

Weee Directive

Yes

5 years



