

09 Track Lights>The COB Zoomable Cylinders

## 65650BT/W/W



20W adjustable beam 20°-60° track spot with COB LED, ideal for shops and showrooms.

Supplied with electronic high frequency control driver as standard.


Complies with standard EN60598-1 and any other specific standards.



### Downloads



### Dimensions



### Related items



40001A/W



40002A/W




40003A/W


### Physical Specification

Item Group	09 Track Lights
Family	The COB Zoomable Cylinders
Order Code	65650BT/W/W
Colour	White
Material	Die Cast
Diffuser Material	Plastic
Shape	Circular


Height	120mm
Diameter	75mm
Track mounted	Yes
Indoor	Yes
Adjustable	2 Directions

## Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	20W
IP Rating	IP20
Light Source	LED built in
Dimmable	No

Fitting	
Input Type	Constant Current
Input Current	500mA
Safety Class	
IP Rating	IP20
Light Source	LED built in
LED Type	COB
LED Brand	Bridgelux

Gear	
Gear Type	Led Driver
Input Voltage	220-240V

50 Hz	Yes
60 Hz	Yes
Constant Current	Yes
500mA	36V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	50°C
Operating Temp	80°C
Housing Material	Plastic
Output Terminal	Connector
Brand	Vossloh-Schwabe
Protection	Short Circuit Protection

#### Illumination Data

Colour Temperature	3000K
Lumen Output	2000lm
Light Efficiency	100lm/W
CRI	90
Beam Angle	20°-60°
Illumination Diagram	

#### Packing Info

Box Weight	0.726kg
Pcs/Carton	15
Barcode	5291889078302
HS Code	9405413990

#### Certification & Warranty

Warranty

5 years

Weee Directive

Yes

switch to  
**one light!**

one  
LIGHT

