



# **Product Datasheet**

09 Track Lights>The COB Zoomable Cylinders

## 65650CT/B/W



30W adjustable beam 20°-60° track spot with COB LED, ideal for shops and showrooms.

Supplied with electronic high frequency control driver as standard.

Complies with standard EN60598-1 and any other specific standards.











Downloads









Dimensions



#### Related items







40002A/B



40003A/B

#### **Physical Specification**

Item Group	09 Track Lights
Family	The COB Zoomable Cylinders
Order Code	65650CT/B/W
Colour	Black
Material	Die Cast
Diffuser Material	Plastic
Shape	Circular

Height	135mm
Diameter	80mm
Track mounted	Yes
Indoor	Yes
Adjustable	2 Directions
lectrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	30W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
Fitting	
Input Type	Constant Current
Input Current	700mA
Safety Class	
IP Rating	IP20
Light Source	LED built in
LED Type	СОВ
LED Brand	Bridgelux
Gear	
Gear Type	Led Driver
Input Voltage	220-240V

50 Hz	Yes
60 Hz	Yes
Constant Current	Yes
700mA	36V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	50°C
Operating Temp	80°C
Housing Material	Plastic
Output Terminal	Connector
Brand	Vossloh-Schwabe
Protection	Short Circuit Protection
umination Data	
umination Data	
umination Data	
Colour Temperature	3000K
	3000K 3000lm
Colour Temperature	
Colour Temperature  Lumen Output	3000lm
Colour Temperature  Lumen Output  Light Efficiency	3000lm 100lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI	3000lm 100lm/W 90
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	3000lm 100lm/W 90
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	3000lm 100lm/W 90
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	3000lm 100lm/W 90
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	3000lm 100lm/W 90
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	3000lm  100lm/W  90  20°-60°
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  acking Info  Box Weight	3000lm  100lm/W  90  20°-60°  0.880kg
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  acking Info  Box Weight  Pcs/Carton	3000lm  100lm/W  90  20°-60°  0.880kg  15

### Certification & Warranty

Warranty

Weee Directive

Yes

5 years



