



Product Datasheet

14 Plafo>Outdoor Project LED Plafo Die cast

67384A/AN/W



30W LED slim plafo, IP54, ideal for both indoor and outdoor installation.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.











Downloads










Dimensions



Physical Specification

| Item Group | 14 Plafo |
|-----------------|------------------------------------|
| Family | Outdoor Project LED Plafo Die cast |
| Order Code | 67384A/AN/W |
| Colour | Anthracite |
| Material | Die Cast |
| Shape | Rectangular |
| Length | 340mm |
| Width | 340mm |
| Height | 50mm |
| Surface Ceiling | Yes |
| Indoor | Yes |
| Outdoor | Yes |

Electrical Characteristics

| Gear | Built In |
|------------------|------------------|
| | |
| Fitting + Driver | |
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Safety Class | |
| Power(Watts) | 30W |
| IP Rating | IP54 |
| Light Source | LED built in |
| Dimmable | No |
| F Mark | F |
| | |
| Fitting | |
| Input Type | Constant Current |
| Input Current | 700mA |
| Voltage | 55V |
| Power(Watts) | 19,25W |
| IP Rating | IP54 |
| Light Source | LED built in |
| LED Type | SMD |
| LED Brand | Osram |
| LED Number | 299 |
| F Mark | F |
| | |
| Gear | |
| Gear Type | Led Driver |
| Input Voltage | 220-240V |

| 50 Hz | Yes |
|----------------------|---------------|
| 60 Hz | Yes |
| Power(Watts) | 21-29,4W |
| Power Factor | 0,9 |
| Constant Current | Yes |
| 700mA | 30-42V |
| IP Rating | IP20 |
| Safety Class | |
| Dimmable | No |
| Housing Material | Plastic |
| Output Terminal | Cable |
| Brand | Eaglerise |
| umination Data | |
| | |
| Colour Temperature | 3000K |
| Lumen Output | 2500lm |
| Light Efficiency | 83,33lm/W |
| CRI | 80 |
| Illumination Diagram | |
| | |
| acking Info | |
| | |
| Box Length | 25,5cm |
| Box Width | 25,5cm |
| Box Height | 6,5cm |
| Box Weight | 2.825kg |
| Pcs/Carton | 4 |
| Barcode | 5291889046615 |
| | |
| HS Code | 9405413990 |

Certification & Warranty

switch to one light!

