



Product Datasheet

13 Wall & Ceiling LED>Outdoor Wall Lights

67492/AN/W



12W LED Wall light.

Complete with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



Physical Specification

Item Group	13 Wall & Ceiling LED
Family	Outdoor Wall Lights
Order Code	67492/AN/W
Colour	Anthracite
Material	Plastic
Diffuser Material	PC
Shape	Rectangular
Length	170mm
Width	140mm
Height	170mm
Surface Wall	Yes
Indoor	Yes

Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	12W
IP Rating	IP54
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	300mA
Voltage	38V
Power(Watts)	11,6W
IP Rating	IP54
Light Source	LED built in
LED Type	SMD 2835
150 D	
LED Brand	Epistar
LED Brand	Epistar
Gear	Epistar
	Epistar Led Driver
Gear	
Gear Gear Type	Led Driver

Colour Temperature Lumen Output CRI BO Illumination Diagram 3000K 600Im 50Im/W 50Im/W	Power(Watts)	6-12W
20-40V 2	Power Factor	0,5
IP Rating Safety Class □ Dimmable No Housing Material Output Terminal Brand Colour Temperature Colour Temperature Lumen Output Light Efficiency CRI Blumination Diagram Packing Info Box Weight Pes/Carton Barcode IP20 No Postic Another Postic Cable Cable Saferise Another Safety Class Solom S	Constant Current	Yes
Safety Class Dimmable Housing Material Output Terminal Brand Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Secking Info Box Weight Pess/Carton Box Weight Pess/Carton Elegierise Illumination Diagram No No Cable Eaglerise Eaglerise Eaglerise Ano Ano Ano Ano Ano Ano Ano An	300mA	20-40V
Dimmable Housing Material Plastic Output Terminal Cable Brand Colour Temperature Lumen Output Light Efficiency CRI Blumination Diagram Box Weight Pes/Carton Barcode No Cable Plastic Cable Plastic Output Cable Ca	IP Rating	IP20
Housing Material Output Terminal Erand Brand Colour Temperature Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Plastic Cable Eaglerise 3000K 600Im 600Im 80 Illumination Diagram Packing Info Box Weight Pes/Carton 12 5291889066170	Safety Class	
Output Terminal Brand Brand Colour Temperature Colour Temperature Lumen Output Light Efficiency CRI Blumination Diagram Box Weight Pes/Carton Barcode Cable Eaglerise Augustins Augustins Augustins Colour Temperature Augustins Augustins Augustins Augustins Colour Temperature Augustins	Dimmable	No
Brand Eaglerise	Housing Material	Plastic
Colour Temperature Lumen Output Light Efficiency CRI Box Weight Pes/Carton Barcode 3000K 600Im 50Im/W 80 0.875kg 12 5291889066170	Output Terminal	Cable
Colour Temperature 3000K Lumen Output 600lm Light Efficiency 50lm/W CRI 80 Illumination Diagram Illumination Diagram Packing Info 0.875kg Pcs/Carton 12 Barcode 5291889066170	Brand	Eaglerise
Colour Temperature Lumen Output CRI Bo Box Weight Pcs/Carton Barcode 3000K 600Im 80 80 80 80 80 80 80 80 80 8		
Lumen Output Light Efficiency CRI Bo Box Weight Pcs/Carton Barcode 600lm 50lm/W 80 0.875kg 12 5291889066170	Illumination Data	
Lumen Output Light Efficiency CRI Bo Box Weight Pcs/Carton Barcode 600lm 50lm/W 80 0.875kg 12 5291889066170		
Light Efficiency CRI BO Fracking Info Box Weight Pcs/Carton Barcode 50Im/W 80 0 80 0 0 1 1 80 1 80 1 80 1 80 1 80 80	Colour Temperature	3000K
CRI Illumination Diagram Packing Info Box Weight Pcs/Carton Barcode 80 0.875kg 12 5291889066170	Lumen Output	600lm
Packing Info Box Weight Pcs/Carton 12 Barcode 5291889066170	Light Efficiency	50lm/W
Packing Info 0.875kg Box Weight 0.875kg Pcs/Carton 12 Barcode 5291889066170	CRI	80
Box Weight 0.875kg Pcs/Carton 12 Barcode 5291889066170	Illumination Diagram	
Box Weight 0.875kg Pcs/Carton 12 Barcode 5291889066170		
Box Weight 0.875kg Pcs/Carton 12 Barcode 5291889066170	Packing Info	
Pcs/Carton 12 Barcode 5291889066170		
Barcode 5291889066170	Box Weight	0.875kg
	Pcs/Carton	12
HS Code 9405114090	Barcode	5291889066170
	HS Code	9405114090

Certification & Warranty

Warranty	2 Years
Weee Directive	Yes



