

Product Datasheet

www.1-light.eu

20 Garden & Underwater>The Project Bollard Range Die cast

67510A/AN/C



20W LED Bollard, IP65 for Garden illumination.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



Accessories



050210/AN

Physical Specification

Item Group	20 Garden & Underwater
Family	The Project Bollard Range Die cast
Order Code	67510A/AN/C
Colour	Anthracite
Material	Die Cast
Shape	Circular

Height	600mm
Diameter	160mm
Surface Floor/Ground	Yes
Outdoor	Yes
Adjustable	No
IK Rating	10
Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	20W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	500mA
Voltage	32,8V
Power(Watts)	16,4W
IP Rating	IP65
Light Source	LED built in

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	20W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
	Constant Current 500mA
Input Type	
Input Type Input Current	500mA
Input Type Input Current Voltage	500mA 32,8V
Input Type Input Current Voltage Power(Watts)	500mA 32,8V 16,4W
Input Type Input Current Voltage Power(Watts) IP Rating	500mA 32,8V 16,4W IP65
Input Type Input Current Voltage Power(Watts) IP Rating Light Source	500mA 32,8V 16,4W IP65 LED built in
Input Type Input Current Voltage Power(Watts) IP Rating Light Source LED Type	500mA 32,8V 16,4W IP65 LED built in SMD 2835

Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	15-21W
Power Factor	0,9
Constant Current	Yes
500mA	30-42v
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	55°C
Operating Temp	85°C
Housing Material	Plastic
Output Terminal	Connector
Brand	HEP
Protection	Short Circuit
Illumination Data	
Colour Temperature	4000K
Lumen Output	2000lm
Light Efficiency	100lm/W
CRI	80
Illumination Diagram	
Packing Info	
Box Weight	4.850kg
Pcs/Carton	2
Barcode	5291889069072

Certification & Warranty

Warranty 2 years



