



Product Datasheet

New 2021 Edition 2>Garden & Underwater

67514/AN/W



6W LED spot, IP65, supplied with spike, for garden illumination.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads










Dimensions



Physical Specification


Item Group	New 2021 Edition 2
Family	Garden & Underwater
Order Code	67514/AN/W
Colour	Anthracite
Material	Aluminium
Shape	Rectangular
Length	100mm
Width	80mm
Height	110mm
Surface Ceiling	Yes
Surface Wall	Yes
Surface Floor/Ground	Yes

Outdoor	Yes
Adjustable	1 Direction
IK Rating	7
Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	6W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
Cable Length	200cm
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	700mA
Voltage	6V
Power(Watts)	4,2W
IP Rating	IP65
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Osram
LED Number	4

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	2-6,3W
Power Factor	0,9
Constant Current	Yes
700mA	2,8-9V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Brand	Eaglerise
Protection	Short Circuit
Illumination Data	
Colour Temperature	3000K
	3000K 550lm
Colour Temperature	
Colour Temperature Lumen Output	550lm
Colour Temperature Lumen Output Light Efficiency	550lm 91,67lm/W
Colour Temperature Lumen Output Light Efficiency CRI	550lm 91,67lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	550lm 91,67lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	550lm 91,67lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	550lm 91,67lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	550lm 91,67lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	550lm 91,67lm/W 80 30°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length	550lm 91,67lm/W 80 30°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width	550lm 91,67lm/W 80 30° 15,5cm 9,5cm

Energy Label



Certification & Warranty

Warranty 2 Years

Weee Directive Yes

switch to one light!

