



Product Datasheet

13 Wall & Ceiling LED>Linear Outdoor Series Double Sided

67526B3/AN/W



2x13W Wall light, IP65.

Complete with 700mA driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads







Dimensions



Physical Specification

Item Group	13 Wall & Ceiling LED
Family	Linear Outdoor Series Double Sided
Order Code	67526B3/AN/W
Colour	Anthracite
Material	Die Cast
Shape	Rectangular
Length	500mm
Width	76mm
Height	66mm
Surface Wall	Yes
Indoor	Yes
Outdoor	Yes

Adjustable	No
IK Rating	7
Floatrical Charactaristics	
Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	2x13W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	700mA
Voltage	17,44V
Power(Watts)	24,42W
IP Rating	IP65
Light Source	LED built in
LED Type	SMD 3030
LED Brand	Osram
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes

60 Hz	Yes
Power(Watts)	26,6-30,1W
Power Factor	0,9
Constant Current	Yes
700mA	28-43V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Brand	Eaglerise
Protection	0
Illumination Data	
Illumination Data Colour Temperature	3000K
Colour Temperature	3000K 1560lm
Colour Temperature Lumen Output	1560lm
Colour Temperature Lumen Output Light Efficiency	1560lm 60lm/W
Colour Temperature Lumen Output Light Efficiency CRI	1560lm
Colour Temperature Lumen Output Light Efficiency	1560lm 60lm/W
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram	1560lm 60lm/W
Colour Temperature Lumen Output Light Efficiency CRI	1560lm 60lm/W
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram	1560lm 60lm/W
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram	1560lm 60lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Weight	1560lm 60lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Weight Pcs/Carton	1560lm 60lm/W 80 2.600kg

Certification & Warranty

switch to one light!

