

21 Industrial & Floodlights>The LED Park Lantern Die cast

70105/AN/C



LED outdoor light for poles 3m and higher. Ideal for parks, parkings, playgrounds.

Supplied with non-dimmable driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads





Dimensions



Physical Specification

Item Group	21 Industrial & Floodlights
Family	The LED Park Lantern Die cast
Order Code	70105/AN/C
Colour	Anthracite
Material	Die Cast
Shape	Circular
Height	511mm
Diameter	460mm
Surface Floor/Ground	Yes
Outdoor	Yes
Adjustable	No


Gear	Built In
Fitting + Driver	
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	50W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
F Mark	

Fitting	
Input Type	Constant Current
Input Current	1700mA
Voltage	29V
Power(Watts)	49W
IP Rating	IP65
Light Source	LED built in
LED Type	COB
LED Brand	Epistar

Gear	
Gear Type	Led Driver
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	46-61,2W
Power Factor	0,9

Constant Current	Yes
1700mA	27-36V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Brand	Meanwell


Illumination Data

Colour Temperature	4000K
Lumen Output	4000lm
Light Efficiency	80lm/W
CRI	70
Beam Angle	60°
Illumination Diagram	

Packing Info

Box Weight	10,4Kg
Pcs/Carton	1
Barcode	5291889047469
HS Code	9405409900

Energy Label



Warranty

5 Years

Weee Directive

Yes

switch to
one light!

one
LIGHT

